Carbon nanotube film and graphene as electron-blocking-layer and transparent electrode for various solar cells

Shigeo Maruyama^{1*,2}

^{1*} Department of Mechanical Engineering, The University of Tokyo, 7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan

² Energy NanoEngineering Lab., National Institute of Advanced Industrial Science and Technology (AIST), 1-2-1 Namiki, Tsukuba 305-8564, Japan

^{1*} Tel: +81-3-5841-6421, E-mail: maruyama@photon.t.u-tokyo.ac.jp

It was found that a film of single-walled carbon nanotubes (SWNTs) can be a dual-functional layer as electron-blocking-layer and transparent electrode through studies of nanotube-silicon heterojunction solar cells [1-3]. We have demonstrated efficient SWNT/Si solar cells using dry-deposited high-quality SWNTs [1] and honeycomb-structured SWNTs [2]. The SWNT/Si solar cells using the dry deposited SWNT film demonstrated the air-stable power conversion efficiency (PCE) of 11.6 % before any intentional doping process. With the stable copper oxide based doping, the PCE can be more than 13.5 %. Another long-term air stable doping using Lewis acid is also introduced. Adequately doped mm scale single crystal graphene [3] also exhibited the similar performance [4]. The dual functionality is also demonstrated for organic and perovskite solar cells. For organic solar cells, the SWNT/MoO_x/PEDOT:PSS layer was demonstrated as a dual functional layer replacing ITO and organic electron-blocking-layer. Using PTB7/PC71BM mixture as active materials, the PCE of 6 % was obtained for glass substrate and 3.9 % on flexible PET substrate [5]. The dual-functional feature was also demonstrated in double-sided illumination perovskite solar cells using SWNT film instead of electron-blocking-layer and gold electrode with over 9 % PCE [6]. Another perovskite solar cell structure using SWNTs instead of ITO is also proposed [7].

References

[1] K. Cui, T. Chiba, S. Omiya, T. Thurakitseree, P. Zhao, S. Fujii, H. Kataura, E. Einarsson, S. Chiashi, S. Maruyama, J. Phys. Chem. Lett., 4 (2013), 2571.

[2] K. Cui, A. S. Anisimov, T. Chiba, S. Fujii, H. Kataura, A. G. Nasibulin, S. Chiashi, E. I. Kauppinen, S. Maruyama, J. Mater. Chem. A, 2 (2014) 11311.

[3] X. Chen, P. Zhao, R. Xiang, S. Kim, J. Cha, S. Chiashi, S. Maruyama, Carbon, 94 (2015) 810.

[4] K. Cui, S. Maruyama, IEEE Nanotechnology Magazine, 10 (2016) 34.

[5] I. Jeon, K. Cui, T. Chiba, A. Anisimov, A. Nasibulin, E. Kauppinen, S. Maruyama, Y. Matsuo, J. Am. Chem. Soc., 137 (2015) 7982.

[6] T. Chiba, T. Sakaguchi, A. G. Nasibulin, E. I. Kauppinen, R. Xiang, S. Chiashi, S. Maruyama, to be submitted.

[7] I. Jeon, T. Chiba, C. Delacou, Y. Guo, A. Kaskela, O. Reynaud, E. I. Kauppinen, S. Maruyama, Y. Matsuo, Nano Letters, 15 (2015) 6665.